

GLORY T8 ELECTRONIC BALLAST SPECIFICATION

01

T8 New Professional Electronic Ballast

Model No.	P118B	P136B	P158B	P218B
Art.No.	01101-21181X	01101-21361X	01101-21581X	01101-22181X
Lamp Type	1X18W/T8	1X36W/T8	1X58W/T8	2X18W/T8
Voltage Rating	AC220~240V	AC220~240V	AC220~240V	AC220~240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Line Current	0.08 A	0.16 A	0.27 A	0.16 A
Power Factor (λ)	0.98	0.98	0.98	0.98
Dimension(L*W*H)	200 x 27 x 27 mm	200 x 27 x 27 mm	200 x 27 x 27 mm	200 x 27 x 27 mm
Start mode	instant	instant	instant	instant
Packing	50 pcs/ctn	50 pcs/ctn	50 pcs/ctn	50 pcs/ctn
Weight	6.5 / 7 kg	6.7 / 7.2 kg	7.3 / 7.8 kg	6.8 / 7.3 kg
MEAS	305 x 215 x 165 mm	305 x 215 x 165 mm	305 x 215 x 165 mm	305 x 215 x 165 mm

T8 New Professional Electronic Ballast

FEATURE

2013 New Design
 SMT workmanship
 With abnormally protection
 Low power loss and high credibility
 Small Size, Cost Effective
 Ballast Lifetime = 30,000 hrs
 Energy efficiency index EEI=A2
 Certificate: TUV CE


02



GLORY T8 ELECTRONIC BALLAST SPECIFICATION

03

Model No.	P236B
Art.No.	01101-22361Y
Lamp Type	2X36W/T8
Voltage Rating	AC220~240V
Frequency	50/60Hz
Line Current	0.32 A
Power Factor (λ)	0.98
Dimension(L*W*H)	210 x 37 x 28 mm
Start mode	instant
Packing	40 pcs/ctn
Weight	9.3 / 9.8 kg
MEAS	330 x 225 x 175 mm



T8 New Professional Electronic Ballast



04

Model No.	P258B
Art.No.	01101-225813
Lamp Type	2X58W/T8
Voltage Rating	AC220~240V
Frequency	50/60Hz
Line Current	0.52 A
Power Factor (λ)	0.98
Dimension(L*W*H)	280 x 34 x 30 mm
Start mode	instant
Packing	50 pcs/ctn
Weight	12.3 / 12.8 kg
MEAS	365 x 295 x 170 mm